


Supplier's name or trade mark: Luminans			
Model identifier: JP-G95FWB			
Lighting technology used:	LED	Non-directional or directional:	Non-directional
Light source cap-type (or other electric interface)	E27		
Mains or non-mains:	Mains	Connected light source (CLS):	yes
Colour-tuneable light source:	yes	Envelope:	No
High luminance light source:	no		
Anti-glare shield:	no	Can be used with dimmer:	No
Product parameters			
Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000h) rounded up to the nearest integer	7	Energy efficiency class	E
Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	806LM in a sphere (360°),	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2700-6500
On-mode power (P_{on}), W	7	Standby power (P_{sb}), expressed in W and rounded to the second decimal	na
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	0.41	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)	Height	138	Spectral power distribution in the range 250 nm to 800 nm, at full-load 
	Width	95	
	Depth	95	
Claim of equivalent power (c)	yes	If yes, equivalent power (W)	60
		Chromaticity coordinates (x and y)	0.459 / 0.417

Parameters for directional light sources:			
Peak luminous intensity (cd)		Beam angle in degrees, or the range of beam angles that can be set	
Parameters for LED and OLED light sources:			
R9 colour rendering index value	4	Survival factor	90%
the lumen maintenance factor	93.10%		
Parameters for LED and OLED mains light sources:			
displacement factor (cos ϕ_1)	0.5	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	NO	If yes then replacement claim (W)	NA
Flicker metric (Pst LM)	0.103	Stroboscopic effect metric (SVM)	0.085