## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's name or trade mark: LUTEC |  |
|--------------------------------------|--|
|--------------------------------------|--|

Supplier's address: LUTEC EUROPE NV, Herentalsebaan 425, 2160 Wommelgem Wommelgem, BE

| _    | •   |       |                 |   |
|------|-----|-------|-----------------|---|
| Typa | Λt  | liaht | source          | • |
| IVDE | VI. | HEILL | <b>3</b> Uul CE |   |

| Lighting technology used:     | LED     | Non-directional or directional: | NDLS |
|-------------------------------|---------|---------------------------------|------|
| Light source cap-type         | Welding |                                 |      |
| (or other electric interface) |         |                                 |      |
| Mains or non-mains:           | MLS     | Connected light source (CLS):   | No   |
| Colour-tuneable light source: | No      | Envelope:                       | -    |
| High luminance light source:  | No      |                                 |      |
| Anti-glare shield:            | No      | Dimmable:                       | No   |

## **Product parameters**

| Parameter                            |  | Value                     | Parameter  | Value        |
|--------------------------------------|--|---------------------------|--|--------------|
|                                      |  | General product p         | arameters:   |              |
|                                      | mption in on-<br>100 h), rounded<br>st integer                             | 11                        | Energy efficiency<br>class   | F            |
| indicating if it r<br>in a sphere (3 | us flux (фuse),<br>efers to the flux<br>60º), in a wide<br>n a narrow cone | 1 000 in<br>Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000        |
| On-mode pexpressed in W              | oower (P <sub>on</sub> ),  | 10,5                      | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal  | 0,00         |
| for CLS, expres                      | dby power (P <sub>net</sub> )<br>ssed in W and<br>second decimal           | -                         | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 80           |
| Outer                                | Height   | 12                        | Spectral power   | See image    |
| dimensions                           | Width  | 30                        | distribution in the in last pag  | in last page |
| without                              | Depth  | 118                       |  |              |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)                      |                      | range 250 nm to 800<br>nm, at full-load |       |
|---|----------------------|---|-------|
| Claim of equivalent power <sup>(a)</sup>  | Yes                  | If yes, equivalent power (W)            | 72    |
|   |                      | Chromaticity                            | 0,440 |
|   |                      | coordinates (x and y)                   | 0,403 |
| Parameters for LED and OLED li  | ght sources:         |   |       |
| R9 colour rendering index value   | 6                    | Survival factor                         | 1,00  |
| the lumen maintenance factor  | 0,96                 |   |       |
| Parameters for LED and OLED n   | nains light sources: |   |       |
| displacement factor (cos φ1)  | 0,70                 | Colour consistency in McAdam ellipses   | 6     |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. |                      | If yes then replacement claim (W)       | -     |
| Flicker metric (Pst LM)   | 1,0                  | Stroboscopic effect metric (SVM)        | 1,0   |

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;

