Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LUTEC	
--------------------------------------	--

Supplier's address: LUTE	C EUROPE NV, Herentalsebaan 425	5, 2160 Wommelgem	Wommelgem, BE
--------------------------	---------------------------------	-------------------	---------------

Model	identifier	5193801012M
IVIUUEI	iuciiliici.	DIDOCUTOISIN

_	•		
Typa	^t	liaht	source:
IVDE	UI.	IIKIIL	source.

Lighting technology used:	LED	Non-directional or directional:	NDLS	
Light source cap-type	Welding			
(or other electric interface)				
Mains or non-mains:	MLS	Connected light source (CLS):	No	
Colour-tuneable light source:	No	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	No	
Dundhist neversative				

Product parameters

Parameter		Value	Parameter	Value
	General product parameters:			
	mption in on- 100 h), rounded st integer	23	Energy efficiency class	F
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	2 400 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode pexpressed in W	oower (P _{on}),	23,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
for CLS, expres	dby power (P _{net}) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	15	Spectral power	See image
dimensions	Width	56	distribution in the	in last page
without	Depth	57		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)			range 250 nm to 800 nm, at full-load	
Claim of equival	ent power ^(a)	Yes	If yes, equivalent power (W)	147
			Chromaticity	0,440
			coordinates (x and y)	0,403
Parameters for I	LED and OLED lig	ht sources:	'	
R9 colour rende	ring index value	6	Survival factor	1,00
the lumen maintenance factor		0,96		
Parameters for LED and OLED mains light sources:				
displacement fa	ctor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6
Claims that a source replaces light source with ballast of a parti	hout integrated	_(b)	If yes then replacement claim (W)	-
Flicker metric (P	st LM)	1,0	Stroboscopic effect metric (SVM)	1,0

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

