

TECHNICAL DATA SHEET

en

Name of product:

Faxe Maintenance Oil

Type of product: Oil based on ennobled vegetable oils and isoparaffin.
Application: Care and maintenance of wooden surfaces, which is treated with naturel curing oil eg. Faxe Wood Oil
Properties: Gives the wood a water and dirt repellent surface. It also retains its natural appearance and color.

Solids: 40 weight % 33 vol. %

Pre-treatment: Clean the wood to remove all grease and dirt. The wood should be dry before further treatment. Faxe Wood Cleaner, which effective removes residues of woodcare products, can be used. Then Faxe Refreshing Oil is applied. The Refreshing Oil is polished into the floor either with a cloth or a polish machine. Remove any excess of oil with dry clothes.

Application:

Method:	Recommended viscosity:	Thinner:
Lint-free rags	No thinning required	-

Drying:

	Drying time	Film thickness - dry
Dry to use	4-8 hours 20 °C	-

Storage: Store cool and dry

Shelf-life: 12 Months in an unopened container

Note: Dont use water on the treatment for the first 3 days.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

Esbjerg Farve- & Lakfabrik A/S

Energivej 13

DK- 6700 Esbjerg

Ph. +45 75 12 86 00 FAX +45 75 45 33 68 e-mail: info@esbjergpaints.dk

www.esbjergpaints.dk