



The pictures may differ in color
from the original product.

Eiche Sunshine

- ◊ Natural wood look
- ◊ Quiet and warm underfoot
- ◊ Only 5 mm mounting height
- ◊ Wear layer 0,3 mm
- ◊ 1210 x 190 mm (L x W)
- ◊ Carton content = 8 planks = 1,84 m²
- ◊ 100% recyclable
- ◊ Simple, floating floor laying
- ◊ Patented Uniclic connection
- ◊ Low emissions (Certified A +)
- ◊ DIBT certified
- ◊ Sound reduction up to 5 dB
- ◊ Utilization class 23/31

Note before laying:

- Amount needed + 10% of the area
- Clean underlay, hard, flat, stable and strong
- Uneven surface = max 3 mm per 1,2 m
- Acclimatize the planks horizontally in the room for at least 48h!
- Important: room temperature = soil temperature = use temperature 18 ° C to 24 ° C

Points to note about the configuration:

- If underlay required: flameproof, vinyl approved (at least 400 kPa/m², 1,5 mm, non-adhesive)
- On linoleum, wood-based flooring: 0,2 mm PE Films building for decoupling mandatory!
- The planks must be properly clicked in!
- Provide expansion joints to walls and fixed objects of 8-10 mm
- Maximum field size 10 x 10 m



Article No.	Description	EAN	Pack/Pallet
2 242 42 06	b!design clic, Eiche Sunshine, 5 mm	0088969754165	32